

Leistungstabellen

Typ SF/E 150 - 1000 Liter

Typ	Reg m ²	VL °C	Spitzen- leistung 45°C l/10 min.	Spitzen- leistung 45°C l/h	Dauer- leistung 45°C l/h	Leistung kW (10 - 45 °C)	Spitzen- leistung 60°C l/10 min.	Spitzen- leistung 60°C l/h	Dauer- leistung 60°C l/h	Leistung kW (10°C - 60°C)	Heiz- wasser Primär m³/h	Druck- verlust mbar	N _L
SF/E 150	1.0	50	127	238	133	5.4	-	-	-	-			
		60	140	314	209	8.5	-	-	-	-			
		70	153	391	286	11.6	132	265	160	9.3			
		80	165	467	362	14.7	141	318	213	12.4	1.3	20	2
SF/E 200	1.4	50	171	327	187	7.6	-	-	-	-			
		60	189	433	293	11.9	-	-	-	-			
		70	207	540	400	16.3	177	364	224	13.0			
		80	224	647	507	20.6	190	439	299	17.4	1.8	40	3
SF/E 300	1.7	50	248	437	227	9.2	-	-	-	-			
		60	269	566	356	14.5	-	-	-	-			
		70	291	696	486	19.8	255	482	272	15.8			
		80	313	825	615	25.0	270	573	363	21.1	2.2	70	4
SF/E 400	2.0	50	324	547	267	10.9	-	-	-	-			
		60	350	699	419	17.1	-	-	-	-			
		70	375	851	571	23.3	333	600	320	18.6			
		80	401	1004	724	29.5	351	707	427	24.8	2.5	110	7
SF/E 500	2.6	50	408	697	347	14.1	-	-	-	-			
		60	441	895	545	22.2	-	-	-	-			
		70	474	1093	743	30.2	419	766	416	24.2			
		80	507	1291	941	38.3	442	905	555	32.2	3.3	230	11
SF/E 600	2.6	50	478	767	347	14.1	-	-	-	-			
		60	511	965	545	22.2	-	-	-	-			
		70	544	1163	743	30.2	489	836	416	24.2			
		80	577	1361	941	38.3	512	975	555	32.2	3.3	230	14
SF/E 800	3.7	50	642	1053	493	20.1	-	-	-	-			
		60	689	1335	775	31.5	-	-	-	-			
		70	736	1617	1057	43.0	659	1152	592	34.4			
		80	783	1899	1339	54.5	692	1349	789	45.9	4.7	160	24
SF/E 1000	3.7	50	782	1193	493	20.1	-	-	-	-			
		60	829	1475	775	31.5	-	-	-	-			
		70	876	1757	1057	43.0	799	1292	592	34.4			
		80	923	2039	1339	54.5	832	1489	789	45.9	4.7	160	26

NL bei HZ 80°C VL und TWW 10°C auf 45°C